

ORBITAL WRAPPING MACHINE NELEO 50

Semiautomatic machine for horizontal packaging with stretchfilm.

Applications:

Packaging, grouping and protection with stretchfilm of products like mouldings, flooring, profiles, aluminium bars tubes, blinds, etc.

Working process:

The user places the product manually until the ring through the infeed gravity rollers conveyor; pressing the footswitch the machine wraps it with stretchfilm. Finally the user take out manually the product fully wrapped through the outfeed gravity rollers conveyor.

Standard equipment:

- Double reel dispenser head; allows to wrap with two reels of stretchfilm for a reinforced wrapping and faster packaging or to wrap with one reel for a simple wrapping; ready to use reels of different width.
- Fast changing reels without tools and with self-fixing system.
- Adjustable stretchfilm tension to fit it to the product, keeping the same tension level from the begin to the end of the reel.
- Device that unable the machine to work while reel changing for worker safety, placed in the access window.
- Ring driver system through trapezoidal belt.
- Ring assembled in the frame, painted in yellow colour.
- Steel frame, painted in grey and base in green colour
- Adjustable rotation ring speed to control the stretchfilm overlap onto the product.
- Safety footswitch to start/finish the wrapping cycle.
- Control panel: Master switch, power light, warning light, reset button, speed controller & emergency stop.
- Packaging in wooden pallet for transport.
- Machine certificate meeting CE safety standards (2006/42/CE, 2004/42/CE & 93/68/CEE).

Accessories (optional):

- Double automatic stretchfilm clamp and cutter system for two reels; cuts even with zero tension and has a blade protector for user safety.
- Packaging programs: manual, automatic and banding (included with cutter system option).
- Infeed & outfeed gravity rollers table with vertical rollers and numerical meter to level easily, for product feeding (suggested).
- Gravity rollers conveyors.
- Side vertical rollers "V" shape.
- Short products bridge.
- Top presser with manual fitting.
- Wheels with brake.
- Manual bubblewrap floor dispenser for reel of >600mm.
- No standard machine colour.
- Seafreight packaging wooden crate or box.



*Mod. with gravity rollers table (optional)





ORBITAL WRAPPING MACHINE NELEO 50

Semiautomatic machine for horizontal packaging with stretchfilm.

Technical specifications:

Product to wrap sizes:	
 Maximum / minimum length 	: no limit / 250mm or 150 mm with short products bridge.
 Width and height 	: Check with graphic.

Electrical equipment:	
• Power	: 230V I.
• Engine	: 0,4 Kw
 Manoeuvre 	: 24V c.c.
 Power consumption 	: 0,26 Kw
 Ring rotation speed 	: from 5 to 150 rpm.
 Speed inverter 	: Omron.
• PLC	: Omron.
 Pneumatic pressure 	: 6 bars (for configuration with cutting system).
 Compressed air consumption 	: 3 liters/cycle (for configuration with cutting system).

Stretchfilm or paper* reel specifications:

• Width : 100 mm.

• Thickness : 17, 20, 23 or 30 microns.

• External / Internal Ø : 200 / 38 mm.


• Colour : Transparent / opaque.

(*) Only for configuration without cutting system.

Installed machine sizes : Check attached drawing.

Packed machine sizes : 1,20 x 0,80 x 1,65 m - 150 Kg.

Packed film reels sizes : 1,00 x 1,20 x 1,97 m - 915 Kg.







Technical specifications are subject to change without notice.



